

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2021/0283329 A1 Murphy et al.

Sep. 16, 2021 (43) **Pub. Date:**

(54) METHOD AND SYSTEM FOR SHAPE-MEMORY ALLOY WIRE CONTROL

(71) Applicant: **DEKA Products Limited Partnership**, Manchester, NH (US)

Inventors: Colin H. Murphy, Cambridge, MA (US); Dean Kamen, Bedford, NH (US); John M. Kerwin, Manchester, NH (US); Larry B. Gray, Merrimack, NH

Appl. No.: 17/185,074

(22) Filed: Feb. 25, 2021

Related U.S. Application Data

- Continuation of application No. 15/633,178, filed on Jun. 26, 2017, now Pat. No. 10,933,187, which is a continuation of application No. 14/507,484, filed on Oct. 6, 2014, now Pat. No. 9,687,602, which is a division of application No. 13/011,384, filed on Jan. 21, 2011, now Pat. No. 8,852,164, which is a continuation-in-part of application No. 12/347,981, filed on Dec. 31, 2008, now Pat. No. 8,496,646, which is a continuation-in-part of application No. 11/704,899, filed on Feb. 9, 2007, now Pat. No. 8,414,522, said application No. 12/347,981 is a continuation-in-part of application No. 11/704,896, filed on Feb. 9, 2007, now Pat. No. 8,585,377, said application No. 12/347, 981 is a continuation-in-part of application No. 11/704,886, filed on Feb. 9, 2007, now Pat. No. 8,545,445, said application No. 12/347,981 is a continuation-in-part of application No. 11/704,897, filed on Feb. 9, 2007, now Pat. No. 8,113,244.
- Provisional application No. 61/297,506, filed on Jan. 22, 2010, provisional application No. 61/018,054, filed on Dec. 31, 2007, provisional application No. 61/018,042, filed on Dec. 31, 2007, provisional application No. 61/017,989, filed on Dec. 31, 2007, provisional application No. 61/018,002, filed on Dec. 31, 2007, provisional application No. 61/018,339, filed on Dec. 31, 2007, provisional application No. 61/023,645, filed on Jan. 25, 2008, provisional appli-

cation No. 61/101,053, filed on Sep. 29, 2008, provisional application No. 61/101,077, filed on Sep. 29, 2008, provisional application No. 61/101,105, filed on Sep. 29, 2008, provisional application No. 61/101, 115, filed on Sep. 29, 2008, provisional application (Continued)

Publication Classification

(51)	Int. Cl.	
	A61M 5/142	(2006.01)
	A61M 5/145	(2006.01)
	A61M 5/168	(2006.01)
	G01F 3/20	(2006.01)
	G01F 13/00	(2006.01)
	G01F 25/00	(2006.01)
	G05D 7/06	(2006.01)
	A61M 5/172	(2006.01)

(52) U.S. Cl.

CPC A61M 5/14224 (2013.01); G05D 7/0635 (2013.01); A61M 5/14586 (2013.01); A61M 5/16809 (2013.01); A61M 5/16886 (2013.01); G01F 3/20 (2013.01); G01F 13/006 (2013.01); G01F 25/0092 (2013.01); G05D 7/0676 (2013.01); G05D 7/0641 (2013.01); A61M 5/172 (2013.01); A61M 2005/14268 (2013.01); A61M 2205/0266 (2013.01); A61M 2205/0294 (2013.01); A61M 2205/18 (2013.01); A61M 2205/3331 (2013.01); A61M 2205/3375 (2013.01); A61M 2205/3546 (2013.01); A61M 2205/3576 (2013.01); A61M 2205/8237 (2013.01); A61M 2206/22 (2013.01); A61M 2209/045 (2013.01); A61M 5/14248 (2013.01)

(57)ABSTRACT

A method for controlling a device using a shape-memory alloy wire is disclosed. The method includes determining an ontime for the shape-memory alloy wire based on a target volume to be pumped by a pump plunger, determining the temperature of the shape-memory alloy wire and adjusting the ontime based on the temperature of the shape-memory alloy wire.

